

AGRIMAX RT 945 - Especificaciones técnicas



Description

AGRIMAX RT 945 se ha proyectado especialmente para los cultivos en hileras, ya que no daña los cultivos y protege la cosecha. Además, sus extraordinarias capacidades de auto-limpieza permiten pasar rápidamente del campo a la carretera, donde AGRIMAX RT 945 demuestra excelentes prestaciones. La carcasa robusta proporciona una excelente estabilidad, tracción excepcional y una durabilidad extraordinaria.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor

Version	STANDARD
Type	TL
Tyre Size	380/90 R 46 (14.9 R 46)
LI/SS	155 A8/B

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1852
Static Loaded Radius (mm)	866
Rolling Circumference (mm)	5648
SRI (mm)	875
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-00797
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	1785	2290	2790	3065	3295	3605	3875	-
40	1785	2290	2790	3065	3295	3605	3875	-
30	1910	2450	2990	3280	3530	3860	4150	-
10	2095	2735	3315	3955	4540	4715	5235	5815

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 18:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..