

AGRIMAX RT 955 - Especificaciones técnicas



Description

AGRIMAX RT 955 es un neumático radial BKT, ideal para las aplicaciones de cultivos en hilera, mientras que algunos tamaños son idóneos también para las actividades de pulverización y los viñedos. El dibujo de la banda de rodamiento con su hombro redondeado garantiza excelentes prestaciones de tracción, estabilidad y propiedades de auto-limpieza. Gracias a la carcasa robusta, AGRIMAX RT 955 ofrece una capacidad de carga elevada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	210/90 R 24 (8.3 R 24)
LI/SS	107 A8/B

Dimensions US Standard

Usa code	94042531
Section Width (inch)	8.4
Overall Diameter (inch)	39.8
Static Loaded Radius (inch)	18.2
Rolling Circumference (inch)	119.2
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001818
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41
30	1010	1170	1330	1510	1690	1850	2010	2150	-
25	1010	1170	1330	1510	1690	1850	2010	2150	-
20	1090	1250	1430	1620	1810	1980	2150	2300	-
5	1490	1720	1910	2110	2330	2560	2980	3140	3230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 5:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..