

## AGRIMAX RT 955 - Especificaciones técnicas



### Description

AGRIMAX RT 955 es un neumático radial BKT, ideal para las aplicaciones de cultivos en hilera, mientras que algunos tamaños son idóneos también para las actividades de pulverización y los viñedos. El dibujo de la banda de rodamiento con su hombro redondeado garantiza excelentes prestaciones de tracción, estabilidad y propiedades de auto-limpieza. Gracias a la carcasa robusta, AGRIMAX RT 955 ofrece una capacidad de carga elevada.

### UM

US Standard

### Construction

RADIAL

### Machinery

Agricultura: Pulverizador • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	230/95 R 32 (9.5 R 32)
LI/SS	128 A8/B

## Dimensions US Standard

Usa code	94026678
Section Width (inch)	9
Overall Diameter (inch)	49.3
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	150
Rim Rec	W 7
Rim Alt	W 8
ECE	E4-106R-000764
TRA Code	R1

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1550	2030	2470	2700	2870	3140	3420	3690	3960	-
25	1550	2030	2470	2700	2870	3140	3420	3690	3960	-
20	1660	2170	2650	2900	3060	3360	3660	3960	4250	-
5	1850	2330	2870	3390	3940	4060	4530	5000	5480	5950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 3:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..