

AGRIMAX RT 955 - Especificaciones técnicas



Description

AGRIMAX RT 955 es un neumático radial BKT, ideal para las aplicaciones de cultivos en hilera, mientras que algunos tamaños son idóneos también para las actividades de pulverización y los viñedos. El dibujo de la banda de rodamiento con su hombro redondeado garantiza excelentes prestaciones de tracción, estabilidad y propiedades de auto-limpieza. Gracias a la carcasa robusta, AGRIMAX RT 955 ofrece una capacidad de carga elevada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	340/85 R 48 (13.6 R 48)
LI/SS	151D/154A8

Dimensions US Standard

Usa code	94059287
Section Width (inch)	13.9
Overall Diameter (inch)	70.7
Static Loaded Radius (inch)	33.7
Rolling Circumference (inch)	219.4
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-005765
TRA Code	R1

Load capacity (lbs)

mph / psi	15	17	20	23	29	35	41	46	52	58	64
40	3270	3660	4110	4500	4950	5260	5790	6240	6620	7000	7610
30	3440	3840	4320	4720	5200	5520	6070	6560	6960	7350	7990
25	3560	3970	4460	4880	5380	5710	6280	6780	7200	7610	8270
20	3770	4210	4730	5170	5700	6040	6660	7190	7620	8060	870
5	4920	5480	6160	6730	7420	7880	8670	9360	9930	10500	11410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 4:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..