

AGRIMAX SPARGO - Especificaciones técnicas



Description

AGRIMAX SPARGO es el neumático BKT específico para aplicaciones de cultivos en hileras, proyectado para reforzar la productividad del terreno y conservarlo a largo plazo. Este neumático posee óptimas cualidades de auto-limpieza y una capacidad de carga superior con el inflado estándar. AGRIMAX Spargo garantiza una óptima tracción, combinada con una fuerte estabilidad tanto en el campo como durante los desplazamientos por carretera.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador

Version	STANDARD
Type	TL
Tyre Size	VF 320/90 R 46
LI/SS	165 D

Dimensions International Standard

Section Width (mm)	323
Overall Diameter (mm)	1743
Static Loaded Radius (mm)	810
Rolling Circumference (mm)	5316
SRI (mm)	825
Rim Rec	W 11
Rim Alt	W 10 ; DW 10 ; W 10 L ; DW 11
ECE	E11-106R-0010077
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2050	2290	2575	2815	2955	3100	3195	3290	3455	3625	3765	3910	4030	4150	4265	4385	4575	4765
From 65 to 40	2215	2475	2785	3040	3195	3350	3455	3555	3735	3915	4070	4255	4355	4485	4610	4740	4945	5150
30	2260	2525	2840	3105	3260	3420	3525	3630	3810	3995	4155	4310	4445	4575	4705	4835	5045	5255
20	2305	2575	2895	3165	3325	3485	3595	3700	3890	4075	4235	4400	4530	4665	4800	4935	5150	5360
10	2440	2720	3060	3345	3515	3685	3800	3910	4110	4310	4480	4650	4790	4930	5075	5215	5440	5665

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..