

AGRIMAX SPARGO - Especificaciones técnicas



Description

AGRIMAX SPARGO es el neumático BKT específico para aplicaciones de cultivos en hileras, proyectado para reforzar la productividad del terreno y conservarlo a largo plazo. Este neumático posee óptimas cualidades de auto-limpieza y una capacidad de carga superior con el inflado estándar. AGRIMAX Spargo garantiza una óptima tracción, combinada con una fuerte estabilidad tanto en el campo como durante los desplazamientos por carretera.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador

| | |
|-----------|----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | VF 320/90 R 46 |
| LI/SS | 165 D |

Dimensions US Standard

| | |
|------------------------------|-------------------------------|
| Usa code | 94075645 |
| Section Width (inch) | 12.7 |
| Overall Diameter (inch) | 68.6 |
| Static Loaded Radius (inch) | 31.9 |
| Rolling Circumference (inch) | 209.3 |
| Rim Rec | W 11 |
| Rim Alt | W 10 ; DW 10 ; W 10 L ; DW 11 |
| ECE | E11-106R-0010077 |
| TRA Code | R1 |

Load capacity (lbs)

| mph / psi | 15 | 17 | 20 | 23 | 26 | 29 | 32 | 35 | 38 | 41 | 44 | 47 | 49 | 52 | 55 | 58 | 61 | 64 |
|---------------------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 4520 | 5050 | 5680 | 6210 | 6520 | 6840 | 7050 | 7260 | 7620 | 8000 | 8300 | 8620 | 8890 | 9150 | 9410 | 9670 | 10090 | 10510 |
| From 40 to 25 | 4890 | 5460 | 6140 | 6710 | 7050 | 7390 | 7620 | 7840 | 8240 | 8640 | 8980 | 9320 | 9610 | 9890 | 10170 | 10450 | 10910 | 11360 |
| 20 | 4990 | 5570 | 6270 | 6850 | 7190 | 7540 | 7780 | 9010 | 8400 | 8810 | 9160 | 9510 | 9800 | 10090 | 10380 | 10660 | 11130 | 11590 |
| 12 | 5090 | 5680 | 6390 | 6980 | 7330 | 7690 | 7930 | 8160 | 8580 | 8990 | 9340 | 9700 | 9990 | 10290 | 10590 | 10880 | 11360 | 11820 |
| 5 | 5380 | 6000 | 6750 | 7380 | 7750 | 8130 | 8380 | 8620 | 9070 | 9510 | 9880 | 10260 | 10560 | 10870 | 11190 | 11500 | 12000 | 12490 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..