

AGRIMAX TERIS - Especificaciones técnicas



Description

Las actuales cosechadoras de elevada potencia requieren neumáticos capaces de soportar máquinas y cargas pesadas sin dañar los cultivos. BKT se compromete a ofrecer las soluciones de neumáticos radiales a la vanguardia para aumentar el rendimiento de su cosecha. AGRIMAX TERIS es el compañero ideal para sus operaciones combinadas. Excelente tracción y elevada capacidad de carga son las dos características fundamentales que se traducen en el mejor rendimiento para todas las operaciones de la cosecha. La protección del flanco y el hombro redondeado incrementan la resistencia – alargando el ciclo de vida del producto – incluso en condiciones adversas aunque hay los rastrojos en el campo.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cosechadora de algodón • Cosechadora

Version	STANDARD
Type	TL
Tyre Size	750/65 R 26 CHO (28L R 26)
LI/SS	166 A8/B

Dimensions International Standard

Section Width (mm)	764
Overall Diameter (mm)	1636
Static Loaded Radius (mm)	713
Rolling Circumference (mm)	4908
SRI (mm)	750
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E4-106R-000810

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4
50	2915	3340	4085	4400	4930	5300
40	2915	3340	4085	4400	4930	5300
30	3125	3580	4370	4715	5280	5675
15 Cyc	4810	5510	6735	7260	8135	8745
10 Cyc	5250	6015	7350	7920	8875	9540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 5:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..