

AIROMAX AM 27 - Especificaciones técnicas



Description

AIROMAX AM 27 es un neumático que se utiliza principalmente por carretera, ideal para las aplicaciones con grúas en el sector de la construcción. Este neumático se caracteriza por su resistencia al calor y excepcional confort. AIROMAX AM 27 es un neumático para utilizarlo con una alta velocidad, particularmente idóneo para todas las operaciones que requieran un elevado nivel de maniobrabilidad.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Grúa móvil

Version	STANDARD
Type	TL
Tyre Size	385/95 R 25 (14.00 R 25)
LI/SS	170 F

Dimensions US Standard

Usa code	94044214
Overall Width (inch)	14.6
Overall Diameter (inch)	53.7
Static Loaded Radius (inch)	24.6
Rolling Circumference (inch)	164.4
Rim Rec	10.00/1.5
ECE	E11-54R-0015911

Load capacity (lbs)

mph / psi	130
50	13200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 0:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..