

ARROW - Especificaciones técnicas



Description

ARROW es idóneo para las aplicaciones de transporte con remolques. Este neumático ha sido desarrollado para utilizarlo principalmente por carretera y asegura un mayor kilometraje y una vida operativa más larga. ARROW ofrece elevada capacidad de carga incluso a altas velocidades. Está disponible también como versión HD que asegura un rendimiento optimizado.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

Version	TRACTOR TRAILER
Type	TT
Tyre Size	9.00 - 20

Dimensions US Standard

Usa code	94045501
Ply Rating	16
Section Width (inch)	10.6
Overall Diameter (inch)	40.9
Rim Rec	7.0
Rim Alt	6.5 ; 7.5

Load capacity (lbs)

mph / psi	105
25	5990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 18:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..