

AS 2001 - Especificaciones técnicas



Description

AS 2001 es un neumático diagonal de telas cruzadas idóneo para los minitractores que se utilizan para los trabajos del campo. Su dibujo asegura una excelente tracción et óptimas propiedades de auto-limpieza. AS 2001 ha sido realizado con una mezcla particularmente resistente a los cortes y los desgarres que proporciona una elevada capacidad de carga.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28
LI/SS	143 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	429
Overall Diameter (mm)	1420
Static Loaded Radius (mm)	651
Rolling Circumference (mm)	4319
SRI (mm)	675
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E4-106R-002045
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.40
30	2725

Printed on 29/08/2024 9:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..