

## AT 109 - Especificaciones técnicas



### Description

AT 109 es un neumático todo terreno para vehículos ATV. El dibujo de la banda de rodadura asegura una excelente protección del campo.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Vehículo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 20 X 7 - 8

## Dimensions International Standard

Ply Rating	2
Section Width (mm)	170
Overall Diameter (mm)	504
Rim Rec	5.5 AT
Rim Alt	6.0 AT
ECE	E11-75R-004669

## Load capacity (Kg)

km/h / bar	0.45
100	100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 17:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..