

## AT 621 - Ficha técnica



### Description

AT 621 es idóneo para las ternas y las palas compactas que se utilizan en todas las operaciones de excavación y carga en el ámbito agrícola. La banda de rodadura del AT 621 es extra profunda, asegurando una excepcional resistencia a los cortes y los desgarros así como una mayor durabilidad. Además, este neumático asegura optimas propiedades de auto-limpieza. AT 621 está disponible en varias versiones con el fin de responder a las diferentes exigencias de los usuarios.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Cargadora compacta • Cargadora retroexcavadora

Industrial: Cargadora retroexcavadora • Pala cargadora

| SIZE                                | Version          | USACode  | TRA Code | LI/SS              | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC            | RIM ALT                    | SW   | OD   | SLR  | RC    | Type | ECE             |
|-------------------------------------|------------------|----------|----------|--------------------|-------------------|--------------------|----|--------------------|----------------------------|------|------|------|-------|------|-----------------|
| 33 X<br>12.5 - 15                   | STANDARD         | 94037209 | R4       |                    |                   |                    | 8  | 10.00 F<br>SDC     |                            | 12.5 | 33.5 | 15.5 | 98.7  | TT   | E11-106R-005230 |
| 10.0/75<br>- 15.3                   | STANDARD         | 94070619 |          | 127 A6             |                   |                    | 10 | 9.0                |                            | 10.5 | 30.7 | 14.7 | 93.9  | TL   | E11-106R-007466 |
| 12.5/70<br>- 16                     | STANDARD         | 94054169 | R4       |                    |                   |                    | 14 | 10 LB              |                            | 12.4 | 33.7 | 15.2 | 101.7 | TL   |                 |
| 12.5/70<br>- 16                     | STANDARD         | 94054350 | R4       |                    |                   |                    | 14 | 10 LB              |                            | 12.4 | 33.7 | 15.2 | 101.7 | TT   |                 |
| 12.5/70<br>- 16                     | STANDARD         | 94028511 | R4       |                    |                   |                    | 8  | 10 LB              |                            | 12.4 | 33.7 | 15.2 | 101.7 | TL   | E11-106R-005295 |
| 9.00 - 16                           | INDUSTRIAL       | 94051595 |          | 137 A6             |                   |                    | 16 | 6.50 H             | 6.00 G                     | 10.2 | 36.4 | 0    | 0     | TT   | E11-106R-005364 |
| 12.5/80<br>- 18                     | INDUSTRIAL<br>HD | 94032730 | R4       |                    | 135 A8            | 148 A8             | 16 | W 9                | 11.0                       | 12.1 | 38.9 | 17.1 | 114.8 | TL   | E11-106R-005365 |
| 12.5/80<br>- 18                     | SPECIAL          | 94035960 | R4       |                    | 129 A8            | 142 A8             | 12 | W 9                | 11.0                       | 12.1 | 38.9 | 17.1 | 114.8 | TL   | E11-106R-005329 |
| 12.5/80<br>- 18                     | STANDARD         | 94019731 | R4       |                    | 129 A8            | 142 A8             | 12 | W 9                | 11.0                       | 12.1 | 38.9 | 17.1 | 114.8 | TL   | E11-106R-003388 |
| 12.5/80<br>- 18                     | STANDARD         | 94019748 | R4       |                    | 135 A8            | 148 A8             | 16 | W 9                | 11.0                       | 12.1 | 38.9 | 17.1 | 114.8 | TT   | E11-106R-006957 |
| 12.5/80<br>- 18                     | STANDARD         | 94026258 | R4       |                    | 135 A8            | 148 A8             | 16 | W 9                | 11.0                       | 12.1 | 38.9 | 17.1 | 114.8 | TL   | E11-106R-006957 |
| 12.5/80<br>- 18                     | STANDARD         | 94019724 | R4       |                    | 129 A8            | 142 A8             | 12 | W 9                | 11.0                       | 12.1 | 38.9 | 17.1 | 114.8 | TT   | E11-106R-003388 |
| 15.5/60<br>- 18                     | STANDARD         | 94028542 | R4       | 139 A2             |                   |                    | 10 | W 13               |                            | 15.5 | 37   | 16.9 | 113   | TL   | E11-106R-003575 |
| 15.5/60<br>- 18                     | STANDARD         | 94048229 | R4       | 141 A2             |                   |                    | 12 | W 13               |                            | 15.5 | 37   | 16.9 | 113   | TL   | E11-106R-004651 |
| 15.5/70<br>- 18<br>(400/70<br>- 18) | STANDARD         | 94041602 | R4       |                    |                   |                    | 10 | W 13               |                            | 15.7 | 40.6 | 18.7 | 122.5 | TL   | E11-106R-005260 |
| 385/65<br>D 19.5                    | STANDARD         | 94065912 |          | 165 A2             |                   |                    | 16 | 11.75              | 12.25                      | 15.4 | 40.2 | 18.8 | 123.5 | TL   | E11-106R-006419 |
| 12.5 - 20                           | STANDARD         | 94058488 | R4       |                    |                   |                    | 12 | 11.0               |                            | 12.8 | 40.9 | 0    | 0     | TT   | E11-106R-005293 |
| 17.5/65<br>- 20                     | STANDARD         | 94028559 | R4       |                    |                   |                    | 10 | W 14 L             |                            | 17.7 | 42.9 | 19.3 | 129.7 | TL   | E11-106R-005262 |
| 400/70 -<br>20                      | STANDARD         | 94060658 | R4       | 152<br>B/168<br>A2 |                   |                    | 16 | 13                 | 12 SDC ;<br>13 SDC ;<br>14 | 15.9 | 42.9 | 19.4 | 128.8 | TL   |                 |
| 400/70 -<br>20                      | STANDARD         | 94051526 | R4       | 149 A8             |                   |                    |    | 13                 | 12 SDC ;<br>13 SDC ;<br>14 | 15.9 | 42.9 | 19.4 | 128.8 | TL   | E11-106R-005289 |
| 42 X 17<br>- 20                     | STANDARD         | 94037216 | R4       |                    |                   |                    | 10 | 14.00<br>TG<br>SDC |                            | 17   | 42.2 | 18.9 | 125.9 | TT   | E11-106R-005294 |
| 16.9 - 24                           | INDUSTRIAL       | 94035397 | R4       | 149 A8             |                   |                    | 12 | DW 15<br>L         | DW 14 L                    | 17.7 | 51.3 | 23.2 | 153.8 | TL   | E11-106R-005374 |
| 17.5L -                             | STANDARD         | 94027491 | R4       | 139 A8             |                   |                    | 8  | DW 15              | DW 14 L                    | 17.7 | 49.4 | 22   | 147.7 | TL   | E11-            |

|                   |            |          |    |        |    |         |         |      |      |      |       |    |  |                 |             |
|-------------------|------------|----------|----|--------|----|---------|---------|------|------|------|-------|----|--|-----------------|-------------|
| <b>24</b>         |            |          |    |        |    | L       |         |      |      |      |       |    |  |                 | 106R-005267 |
| <b>19.5L - 24</b> | STANDARD   | 94046232 | R4 | 151 A8 | 12 | DW 16 L |         | 19   | 51.4 | 23.1 | 155   | TL |  | E11-106R-005373 |             |
| <b>18.4 - 26</b>  | STANDARD   | 94031801 | R4 | 156 A8 | 12 | DW 16 L | DW 15 L | 18.9 | 56.1 | 25.6 | 168.8 | TL |  | E11-106R-003634 |             |
| <b>16.9 - 28</b>  | INDUSTRIAL | 94069675 | R4 | 154 A8 | 14 | DW 15 L | DW 14 L | 17.7 | 55.5 | 25.2 | 165.3 | TL |  | E11-106R-007209 |             |
| <b>16.9 - 28</b>  | INDUSTRIAL | 94016792 | R4 | 152 A8 | 12 | DW 15 L | DW 14 L | 17.7 | 55.5 | 25.2 | 165.3 | TT |  | E11-106R-003635 |             |
| <b>16.9 - 28</b>  | INDUSTRIAL | 94016808 | R4 | 152 A8 | 12 | DW 15 L | DW 14 L | 17.7 | 55.5 | 25.2 | 165.3 | TL |  | E11-106R-003635 |             |
| <b>16.9 - 30</b>  | INDUSTRIAL | 94027507 | R4 | 153 A8 | 12 | DW 15 L | DW 14 L | 17.7 | 57.5 | 26.4 | 173.1 | TL |  | E11-106R-005375 |             |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 13:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..