

AW-18 - Especificaciones técnicas



Description

AW-18 se ha diseñado para los remolques y la maquinaria agrícola utilizada para las labores del campo. Su diseño especial, con tacos no direccionales y una zona de hombro redondeado, evita los daños a los cultivos al maniobrar. El dibujo de la banda de rodadura se ha desarrollado específicamente para garantizar las mejores propiedades de autolimpieza. AW-18 destaca asimismo por una gran comodidad de conducción y un consumo de combustible reducido.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Maquinaria agrícola

Version	STANDARD
Type	TL
Tyre Size	11.5/80 - 15.3 (300/80 - 15.3)
LI/SS FREE ROLLING	139 A8

Dimensions International Standard

Section Width (mm)	297
Overall Diameter (mm)	845
Rim Rec	9.00
ECE	E11-106R-006020

Load capacity (Kg)

km/h / bar	4.75
10 FR	3400
25 FR	2890
30 FR	2720
40 FR	2430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 18:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..