

AW 705 - Especificaciones técnicas



Description

AW 705 ha sido desarrollado para maquinaria agrícola, remolques y empacadoras de heno que se utilizan en los trabajos del campo y en el transporte. Es idóneo para utilizarlo en la agricultura moderna gracias a durabilidad superior y una capacidad de carga elevada.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	400/55 - 22.5
LI/SS FREE ROLLING	154 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	405
Overall Diameter (mm)	1016
Static Loaded Radius (mm)	443
Rolling Circumference (mm)	3072
Rim Rec	AG 11.75
Rim Alt	12.25 ; AG 13.00
ECE	E11-106R-004550

Load capacity (Kg)

km/h / bar	4.50
10 FR	5250
25 FR	4465
30 FR	4200
40 FR	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 2:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..