

## AW 909 - Ficha técnica



### Description

AW 909 ha sido desarrollado para los trabajos del campo la recogida de heno y en el transporte. Este neumático es ideal para utilizarlo en la agricultura moderna tanto por carretera como fuera de la carretera.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Empacadora de heno • Maquinaria agrícola • Remolque

SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.0 / 75 - 12	STANDARD	94044870	116 A8	8	9.00	7.0	10.4	28	12.3	81.9	TL	E11-106R-005258
10.0/80 - 12	STANDARD	94010493	116 A8	8	9.00	7.0	10.4	28	12.3	81.9	TL	E4-106R-002663
10.0/80 - 12	STANDARD	94010547	121 A8	10	9.00	7.0	10.4	28	12.3	81.9	TL	E4-106R-002662
10.0/75 - 15.3	STANDARD	94010424	126 A8	12	9.00		10.8	29.9	13.5	87.7	TL	E4-106R-001541
10.0/75 - 15.3	STANDARD	94010448	130 A8	14	9.00		10.8	29.9	13.5	87.7	TL	E4-106R-001544
10.0/75 - 15.3	STANDARD	94010462	135 A8	18	9.00		10.8	29.9	13.5	87.7	TL	E4-106R-001880
10.0/75 - 15.3	STANDARD	94010394	123 A8	10	9.00		10.8	29.9	13.5	87.7	TL	E4-106R-001540
11.5/80 - 15.3	STANDARD	94010677	141 A8	16	9.00		11.8	33.2	14.6	97.4	TL	E4-106R-002752
11.5/80 - 15.3	STANDARD	94010707	143 A8	18	9.00		11.8	33.2	14.6	97.4	TL	E4-106R-001881
11.5/80 - 15.3	STANDARD	94010585	131 A8	10	9.00		11.8	33.2	14.6	97.4	TL	E4-106R-001893
11.5/80 - 15.3	STANDARD	94010615	135 A8	12	9.00		11.8	33.2	14.6	97.4	TL	E4-106R-001895
11.5/80 - 15.3	STANDARD	94010646	139 A8	14	9.00		11.8	33.2	14.6	97.4	TL	E4-106R-001897
11.5/80 - 15.3	STANDARD	94010660	141 A8	16	9.00		11.8	33.2	14.6	97.4	TT	E4-106R-002752
12.5/80 - 15.3	STANDARD	94010721	142 A8	14	9.00		12.3	35	15.2	102.1	TL	E11-106R-003602
15.0/55 - 17	STANDARD	94010752	134 A8	10	13.00	13	15.4	33.5	14.8	98	TL	E4-106R-001546
15.0/55 - 17	STANDARD	94010783	138 A8	12	13.00	13	15.4	33.5	14.8	98	TL	E11-106R-003515
15.0/55 - 17	STANDARD	94010813	141 A8	14	13.00	13	15.4	33.5	14.8	98	TL	E4-106R-001547

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..