

## BK 208 - Especificaciones técnicas



### Description

BK 208 es idóneo para su empleo en remolques y camionetas. Es un neumático especialmente duradero y fiable para utilizarlo tanto en el campo como por la carretera.

### UM

International Standard

### Construction

BIAS

### Machinery

Agricultura: Tractor compacto • Camión ligero • Remolque

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	212
<b>Overall Diameter (mm)</b>	810
<b>Rim Rec</b>	6.00 G

## Load capacity (Kg)

	km/h / bar	7.60
	100 LS	1600
	100 LD	1400

Printed on 02/07/2024 17:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..