

BK-LOADER 53 - Especificaciones técnicas



Description

BK-LOADER 53 es un neumático con cinturones de aramida desarrollado para las palas cargadoras utilizadas en las aplicaciones industriales. El dibujo especial de la banda de rodadura garantiza una óptima estabilidad lateral, además, gracias a la banda de rodadura extra profunda también se obtiene una extraordinaria resistencia al desgaste, a los cortes y a los pinchazos. BK-LOADER 53 se caracteriza por sus excepcionales propiedades de auto-limpieza, así como por su excelente agarre y tracción sobre las superficies mojadas y secas. Por último, este neumático es particularmente adecuado para las operaciones de reciclaje.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Pala cargadora

Version	ARAMID BELTED
Type	TL
Tyre Size	365/70 R 18
LI/SS	146A2/142A4

Dimensions US Standard

Usa code	94074143
Section Width (inch)	14.2
Overall Diameter (inch)	39
Static Loaded Radius (inch)	18
Rolling Circumference (inch)	118.8
Rim Rec	11

Load capacity (lbs)

mph / psi	22	29	36	44	51	58	65	73	80
12	2060	2640	3100	3580	4090	4510	4980	5380	5850
5	2320	2980	3510	4040	4630	5100	5630	6090	6620
STATIC	3690	4740	5580	6420	7370	8110	8940	9680	10520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 12:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..