

BK-LOADER 53 - Especificaciones técnicas



Description

BK-LOADER 53 es un neumático con cinturones de aramida desarrollado para las palas cargadoras utilizadas en las aplicaciones industriales. El dibujo especial de la banda de rodadura garantiza una óptima estabilidad lateral, además, gracias a la banda de rodadura extra profunda también se obtiene una extraordinaria resistencia al desgaste, a los cortes y a los pinchazos. BK-LOADER 53 se caracteriza por sus excepcionales propiedades de auto-limpieza, así como por su excelente agarre y tracción sobre las superficies mojadas y secas. Por último, este neumático es particularmente adecuado para las operaciones de reciclaje.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Pala cargadora

Version	ARAMID BELTED
Type	TL
Tyre Size	405/70 R 18
LI/SS	153A2/149A4

Dimensions International Standard

Section Width (mm)	407
Overall Diameter (mm)	1045
Rim Rec	13
Rim Alt	14 ; 13 SDC; 12 ;12 SDC

Load capacity (Kg)

km/h / bar	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
20 TRANSPORT	1140	1465	1725	1985	2275	2505	2765	2990	3250
10 LOADING	1280	1645	1935	2230	2555	2815	3105	3360	3650
STATIC	2050	2635	3105	3570	4095	4505	4975	5385	5850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 12:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..