

COMMANDER TWIN RIB - Especificaciones técnicas



Description

COMMANDER TWIN RIB es un neumático con una nervadura de la banda de rodadura que presenta 4 costillas y entalladuras en los hombros, asegurando de esta forma una óptima adherencia. El perfil más ancho de la banda de rodadura garantiza una óptima distribución del peso. La carcasa robusta y la mezcla superior de la banda de rodadura proporcionan un ciclo de vida más largo del neumático. COMMANDER TWIN RIB es perfecto para los trabajos del campo y las operaciones de transporte.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Tractor 2WD

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 6.50 - 20 |
| LI/SS | 93 A8 |

Dimensions US Standard

| | |
|-------------------------|-----------------|
| Usa code | 94054015 |
| Ply Rating | 8 |
| TMPH | 1 |
| Section Width (inch) | 7.5 |
| Overall Diameter (inch) | 34.4 |
| Rim Rec | 5.00 F |
| Rim Alt | 4.00 E ; 5.50 F |
| ECE | E11-106R-004258 |
| TRA Code | F2 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 66 |
| 25 | 1440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 0:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..