

DON 2000 - Ficha técnica



Description

DON 2000 es un neumático idóneo para realizar operaciones de transporte con remolques y camionetas tanto por carretera como fuera de carretera. Asegura una extraordinaria durabilidad, así como elevadas prestaciones durante todo el ciclo de vida del producto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Camión ligero • Remolque

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
7.50 - 16	STANDARD	94013876	16	6.00 G	5.50 F	8.5	33.1	0	0	TT
10.00 - 20	INDUSTRIAL TRAILER	94040858	16	7.5	7.0 ; 8.0	11.3	42.5	0	0	TT
10.00 - 20	INDUSTRIAL TRAILER	94043866	18	7.5	7.0 ; 8.0	11.3	42.5	0	0	TT
11.00 - 20	STANDARD	94067725	18	8.0	7.5 ; 8.5	11.5	43.7	20.5	134.4	TT
12.00 - 20	STANDARD	94022540	18	8.5	8.0 ; 9.0	12.4	45.1	21.1	138.5	TT
9.00 - 20	STANDARD	94022571	16	7.0	6.5 ; 7.5	10.6	41.3	0	0	TT
9.00 - 20	TRACTOR TRAILER	94045495	16	7.0	6.5 ; 7.5	10.6	41.3	0	0	TT
12.00 - 24	STANDARD	94022557	18	8.5	8.0 ; 9.0	12.4	49	0	0	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 17:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..