

EARTHMAX CRUSHER HAUL - Especificaciones técnicas



Description

EARTHMAX CRUSHER HAUL es un neumático radial All Steel particularmente proyectado para las aplicaciones de transporte por carretera e fuera de carretera, así como operaciones en las minas. Este neumático se caracteriza para una avanzada durabilidad y un mejor kilometraje. El dibujo de bloques de la banda de rodadura garantiza una excelente tracción. Además, EARTHMAX CRUSHER HAUL ofrece un extraordinario confort de conducción, un elevado nivel de maniobrabilidad y menor fatiga de conductor.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Volquete

Version	STANDARD
Type	TL
Tyre Size	12.00 R 24
LI/SS	160/156 K

Dimensions US Standard

Usa code	94075966
Ply Rating	20
Overall Width (inch)	12.2
Overall Diameter (inch)	48.4
Static Loaded Radius (inch)	22.2
Rolling Circumference (inch)	149
Rim Rec	8.50
Rim Alt	9.00

Load capacity (lbs)

mph / psi	125
68 Single	9900
68 Dual	8800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 23:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..