

EARTHMAX SR 22 AS - Especificaciones técnicas



Description

EARTHMAX SR 22 AS (E-2**/G-2*/L-2**) es un neumático radial All Steel diseñado especialmente para niveladoras, pequeñas cargadoras y camiones en condiciones de hielo y nieve, pero garantiza un rendimiento óptimo en todas las estaciones.

El diseño único de la banda de rodadura, con cortes profundos y cuatro tacos, y los compuestos exclusivos para el invierno ofrecen una frenada superior en hielo o nieve, y evitan que se acumulen piedras durante el uso en todas las estaciones.

La baja relación de huecos y la gran huella de EARTHMAX SR 22 AS proporcionan una tracción y estabilidad excelentes, con un desgaste uniforme y una vida de neumático prolongada.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Motoniveladora • Pala cargadora

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 20.5 R 25 |
| LI/SS | 177 B/161 A8/193 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Overall Width (mm) | 532 |
| Overall Diameter (mm) | 1493 |
| Static Loaded Radius (mm) | 641 |
| Rolling Circumference (mm) | 4324 |
| Rim Rec | 17.00/2.0 |
| Star Rating | **/*/** |
| TRA Code | E2/G2/L2 |

Load capacity (Kg)

| km/h / bar | 1.25 | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 50 | - | - | - | - | - | - | - | - | 5800 | 6150 | 6500 | 6700 | 6900 | 7300 | - | - | - | - | - |
| 40 | 2430 | 2800 | 3150 | 3450 | 3875 | 4125 | 4375 | 4625 | - | - | - | - | - | - | - | - | - | - | - |
| 10 | - | - | - | - | - | - | - | - | - | - | - | - | - | 9750 | 10000 | 10300 | 10900 | 11200 | 11500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..