

EARTHMAX SR 22 - Ficha técnica



Description

EARTHMAX SR 22 (G-2/L-2) es un neumático radial **All Steel** particularmente proyectado para las motoniveladoras y cargadoras que operan en condiciones invernales extremas en la nieve o en el hielo. Los operadores apreciarán la excelente tracción y la extraordinaria estabilidad garantizadas por el dibujo de la banda de rodadura ancho y no-direccional.

UM

US Standard

Construction

RADIAL

Machinery

Industrial: Buldócer • Motoniveladora • Pala cargadora

OTR: Buldócer • Motoniveladora • Pala cargadora

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 R 24	CUT RESISTANT COMPOUND	94048816	G2/L2	*	153 A8/175 A2	8.00 TG	9.00 GR , 10.00 VA	14.4	53.9	24.6	163	TL
15.5 R 25	CUT RESISTANT COMPOUND	94063758	G2/L2	*	146 A8/169 A2	12.00/1.3		15.2	50.2	21.9	151.2	TL
17.5 R 25	CUT RESISTANT COMPOUND	94044092	G2/L2	*	153 A8/176 A2	14.00/1.5		17.8	53.1	23.2	155.5	TL
17.5 R 25	CUT RESISTANT COMPOUND	94052387	E2/L2	**	167 B/182 A2	14.00/1.5		17.8	53.1	23.2	155.5	TL
20.5 R 25	CUT RESISTANT COMPOUND	94040803	G2/L2	*	161 A8/186 A2	17.00/2.0	17.00/1.7	20.7	58.7	25.2	169.9	TL
20.5 R 25	CUT RESISTANT COMPOUND	94052431	E2/L2	**	177 B/193 A2	17.00/2.0	17.00/1.7	20.7	58.7	25.2	169.9	TL
23.5 R 25	CUT RESISTANT COMPOUND	94062911	G2/L2	*	170 A8/195 A2	19.50/2.5		24	63.5	27.9	191.5	TL
23.5 R 25	CUT RESISTANT COMPOUND	94064342	E2/L2	**	185 B/201 A2	19.50/2.5		24	63.5	27.9	191.5	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 20:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..