

EARTHMAX SR 30 - Especificaciones técnicas



Description

EARTHMAX SR 30 (E-3/L-3) es un neumático radial **All Steel** proyectado para un doble empleo, tanto con cargadoras como con volquetes articulados. Los cinturones de acero multiestrato y el dibujo rígido con bloques aseguran una excelente tracción, estabilidad y durabilidad. La especial mezcla resistente al corte, hace que EARTHMAX SR 30 sea la solución ideal para trabajar en condiciones operativas especiales.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 20.5 R 25 |
| LI/SS | 193 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Overall Width (mm) | 529 |
| Overall Diameter (mm) | 1487 |
| Static Loaded Radius (mm) | 663 |
| Rolling Circumference (mm) | 4439 |
| Rim Rec | 17.00/2.0 |
| Rim Alt | 17.00/1.7 |
| Star Rating | ** |
| TRA Code | L3 |

Load capacity (Kg)

| km/h / bar | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 |
|------------|------|-------|-------|-------|-------|-------|
| 10 | 9750 | 10000 | 10300 | 10900 | 11200 | 11500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 21:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..