

EARTHMAX SR 315 - Especificaciones técnicas



Description

EARTHMAX SR 315 es un neumático radial All Steel diseñado especialmente para volquetes rígidos. Ofrece un excelente rendimiento en operaciones de excavación, carga y acarreo en minas.

Está equipado con una fuerte carcasa, reforzada por múltiples cinturones de acero, lo que minimiza la rotura por impacto y los pinchazos por las rocas. Las paredes laterales reforzadas y los contrafuertes de EARTHMAX SR 315 garantizan un excelente rendimiento en condiciones rocosas adversas, minimizando los cortes por las rocas y los daños provocados por la fricción. Su banda de rodadura lisa L-3S reduce la perforación por rocas y piedras. El compuesto EARTHMAX SR 315 se ha diseñado específicamente para garantizar una baja generación de calor y fiabilidad en los servicios mineros subterráneos (UMS).

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Cargadora LHD

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 29
LI/SS	211 A2

Dimensions International Standard

Overall Width (mm)	725
Overall Diameter (mm)	1865
Static Loaded Radius (mm)	830
Rolling Circumference (mm)	5635
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	L3S

Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	16500	17500	18000	18500	19000	19500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 3:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..