

EARTHMAX SR 31 - Especificaciones técnicas



Description

EARTHMAX SR 31 es un neumático All Steel radial particularmente proyectado para dúmpers rígidos y palas cargadoras. Los cinturones de acero multiestrato aseguran una extraordinaria fuerza y estabilidad, mientras que el dibujo no-direccional rígido de bloques garantiza una excelente tracción y maniobrabilidad, incluso sobre un terreno de barro. Además del extraordinario confort en la conducción, EARTHMAX SR 31 se caracteriza también por una mezcla especial de la banda de rodadura, particularmente resistente a los cortes y al calor. La estructura radial de la carcasa ofrece además una baja resistencia al rodamiento, con un consecuente y significativo ahorro de carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Buldócer • Pala cargadora

OTR: Volquete articulado • Buldócer • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/195 A2

Dimensions International Standard

TKPH	200
Overall Width (mm)	612
Overall Diameter (mm)	1607
Static Loaded Radius (mm)	711
Rolling Circumference (mm)	4797
Rim Rec	19.50/2.5
Rim Alt	-
Star Rating	**/*
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	7500	7750	8250	8500	9000	9250
10	10300	10600	11200	11500	12150	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 6:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..