

EARTHMAX SR 34 - Ficha técnica



Description

EARTHMAX SR 34 es un neumático radial All Steel especialmente proyectado para los volquetes rígidos que operan en diversas aplicaciones, como las minas, las canteras, el sector forestal y el transporte. El dibujo no direccional de la banda de rodadura proporciona una excelente tracción y estabilidad en cualquier tipo de terreno. EARTHMAX SR 34 es ideal para manipular cargas pesadas. La sólida carcasa All Steel presenta una excelente resistencia al desgaste y contra cortes y pinchazos. Su talón reforzado y el particular diseño del hombro contribuyen a un ciclo de vida más largo del neumático, incluso en las condiciones de servicio pesado exigentes.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dúmper rígido

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
16.00 R 25	CUT RESISTANT COMPOUND	94070732	E3+	**	177 B	11.25/2.0		17.3	59.4	27.3	180.1	TL	130
16.00 R 25	CUT RESISTANT COMPOUND	94070749	E3+	***	183 B	11.25/2.0		17.3	59.4	27.3	180.1	TL	130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..