

## EARTHMAX SR 43 - Especificaciones técnicas



### Description

EARTHMAX SR 43 (L-4) es un neumático radial All Steel particularmente proyectado para palas de ruedas compactas que operan en condiciones rocosas extremas, principalmente en las minas subterráneas. El neumático garantiza excelentes prestaciones en las operaciones de carga y de transporte en las minas a cielo abierto, en las canteras y en las operaciones de demolición. El diseño único de la banda de rodadura asegura una tracción y una estabilidad superiores. Gracias a la estructura All Steel, EARTHMAX SR 43 (L-4) asegura una excelente robustez y resistencia a las laceraciones y los pinchazos, así como un ciclo de vida más largo.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 29
LI/SS	223 A2

## Dimensions US Standard

Usa code	94051021
Overall Width (inch)	30.2
Overall Diameter (inch)	78.9
Static Loaded Radius (inch)	35.6
Rolling Circumference (inch)	237.4
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5, 26.00/3.5
Star Rating	***
TRA Code	L4

## Load capacity (lbs)

mph / psi	98	102	105	109	112	116
5	53600	55100	56800	57800	58900	60000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..