

EARTHMAX SR 45 M - Ficha técnica

Description

EARTHMAX SR 45 M es un neumático radial **All Steel** particularmente proyectado para los volquetes rígidos. EARTHMAX SR 45 M asegura una óptima tracción y es ideal para las operaciones en largos recorridos.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dúmper rígido



SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
18.00 R 33	CUT RESISTANT COMPOUND	94076543	E4	**	191 B	13.00/2.5	--	19.9	73.6	33.7	220.8	TL	127
18.00 R 33	HEAT RESISTANT COMPOUND	94076550	E4	**	191 B	13.00/2.5	--	19.9	73.6	33.7	220.8	TL	175
18.00 R 33	STANDARD COMPOUND	94076536	E4	**	191 B	13.00/2.5	--	19.9	73.6	33.7	220.8	TL	151
24.00 R 35	CUT RESISTANT COMPOUND	94029907	E4	**	209 B	17.00/3.5	--	26.1	85.8	38.6	257.4	TL	228
24.00 R 35	HEAT RESISTANT COMPOUND	94045921	E4	**	209 B	17.00/3.5	--	26.1	85.8	38.6	257.4	TL	298
24.00 R 35	STANDARD COMPOUND	94032280	E4	**	209 B	17.00/3.5	--	26.1	85.8	38.6	257.4	TL	267

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 12:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..