

EARTHMAX SR 454 - Especificaciones técnicas



Description

EARTHMAX SR 454 es un neumático radial All Steel diseñado especialmente para camiones volquete rígidos. El exclusivo diseño de la banda de rodadura E-3 y el surco central especial proporcionan una mayor tracción lateral y maniobrabilidad tanto en superficies blandas como embarradas. Este neumático está especialmente diseñado para velocidades más altas y trayectos largos a una temperatura de funcionamiento más fría. La construcción All Steel con cinturones de acero multicapa proporciona una protección superior contra los golpes y la penetración de las rocas, para mejorar el tiempo de funcionamiento y, en consecuencia, aumentar la productividad. El hombro cuadrado de EARTHMAX SR 454 maximiza el contacto con el suelo para ofrecer una excelente maniobrabilidad y estabilidad, por no hablar de la reducción de las vibraciones y del ruido.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dúmper rígido

Version	STANDARD COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions US Standard

Usa code	94067800
TMPH	438
Overall Width (inch)	29.1
Overall Diameter (inch)	104.3
Static Loaded Radius (inch)	46.7
Rolling Circumference (inch)	316.5
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 16:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..