

EARTHMAX SR 454 - Ficha técnica



Description

EARTHMAX SR 454 es un neumático radial All Steel diseñado especialmente para camiones volquete rígidos. El exclusivo diseño de la banda de rodadura E-3 y el surco central especial proporcionan una mayor tracción lateral y maniobrabilidad tanto en superficies blandas como embarradas. Este neumático está especialmente diseñado para velocidades más altas y trayectos largos a una temperatura de funcionamiento más fría. La construcción All Steel con cinturones de acero multicapa proporciona una protección superior contra los golpes y la penetración de las rocas, para mejorar el tiempo de funcionamiento y, en consecuencia, aumentar la productividad. El hombro cuadrado de EARTHMAX SR 454 maximiza el contacto con el suelo para ofrecer una excelente maniobrabilidad y estabilidad, por no hablar de la reducción de las vibraciones y del ruido.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dúmpers rígidos

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
27.00 R 49	CUT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	525
27.00 R 49	HEAT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	725
27.00 R 49	STANDARD COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	640
33.00 R 51	CUT RESISTANT COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	884
33.00 R 51	HEAT RESISTANT COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	1215
33.00 R 51	STANDARD COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	1023
40.00 R 57	CUT RESISTANT COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1201
40.00 R 57	HEAT RESISTANT COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1740
40.00 R 57	STANDARD COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1462

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 16:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..