

EARTHMAX SR 468 - Ficha técnica



Description

EARTHMAX SR 468 es un neumático radial All Steel diseñado especialmente para camiones volquete rígidos. Su exclusivo diseño de la banda de rodadura con compuestos especiales la hace perfecta para condiciones mineras duras y rocosas. Sus tacos con ranuras circunferenciales y bloques entrelazados garantizan una disipación eficaz del calor. Además, el robusto hombro cuadrado ayuda a expulsar las piedras sueltas para proteger el neumático contra daños. EARTHMAX SR 468 se ha desarrollado con la tecnología de vanguardia de BKT para soportar cargas pesadas, ofrecer una mayor vida útil y proporcionar resistencia a los cortes y pinchazos de las rocas.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dúmper rígido

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
37.00 R 57	CUT RESISTANT COMPOUND	94069354	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	497
37.00 R 57	HEAT RESISTANT COMPOUND	94069347	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	699
37.00 R 57	STANDARD COMPOUND	94069361	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	582
40.00 R 57	CUT RESISTANT COMPOUND	94068845	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	548
40.00 R 57	HEAT RESISTANT COMPOUND	94067381	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	774
40.00 R 57	STANDARD COMPOUND	94068852	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	651
46/90 R 57	CUT RESISTANT COMPOUND	94070589	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	565
46/90 R 57	HEAT RESISTANT COMPOUND	94070596	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	798
46/90 R 57	STANDARD COMPOUND	94070602	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	671
50/80 R 57	CUT RESISTANT COMPOUND	94075164	E4	**	257 B	32.00/6.0	29.00/6.0	47.4	142.1	62.9	428	TL	651
50/80 R 57	HEAT RESISTANT COMPOUND	94075157	E4	**	257 B	32.00/6.0	29.00/6.0	47.4	142.1	62.9	428	TL	918
50/80 R 57	STANDARD COMPOUND	94074228	E4	**	257 B	32.00/6.0	29.00/6.0	47.4	142.1	62.9	428	TL	774

Printed on 02/07/2024 11:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..