

EARTHMAX SR 47 TP - Ficha técnica



Description

EARTHMAX SR 47 TP (E-4) es un neumático radial All Steel diseñado especialmente para camiones volquete rígidos que funcionan en condiciones que exigen la máxima tracción y resistencia a pinchazos. La profundidad de la banda de rodadura del E-4 garantiza una larga vida útil incluso en trayectos largos, lo que reduce el tiempo de inactividad y aumenta la productividad. EARTHMAX SR 47 TP es perfecto para cualquier tarea que exija tracción y estabilidad, especialmente en terrenos embarrados o resbaladizos. Disponible en compuestos estándar y resistente a los cortes.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Dúmper rígido

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	670	2185	985	6625	TL	377
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5	--	670	2185	985	6625	TL	440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..