

## EARTHMAX SR 47 - Especificaciones técnicas



### Description

EARTHMAX SR 47 (E-4) es un neumático radial **All Steel** particularmente proyectado para los dúmpers rígidos que operan en condiciones en las que se requiere la máxima resistencia contra los cortes y las perforaciones en ambientes rocosos. El dibujo único de la banda de rodadura con una profundidad de E-4 reduce el desgaste, asegurando un ciclo de vida más largo al neumático incluso en los desplazamientos largos. Esto se traduce en una reducción de los tiempos de parada y en un incremento de la productividad. Está disponible con mezcla estándar o resistente a los cortes.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dúmpers rígidos

Version	STANDARD COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	195 B

## Dimensions US Standard

Usa code	94064472
TMPH	140
Overall Width (inch)	20.1
Overall Diameter (inch)	74.2
Static Loaded Radius (inch)	34.1
Rolling Circumference (inch)	223.4
Rim Rec	13.00/2.5
Star Rating	***
TRA Code	E4

## Load capacity (lbs)

mph / psi	105	109	112	116
30	24700	25400	26000	26800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..