



EM 933 SUPER - Ficha técnica



Description

EM 933 SUPER se ha diseñado especialmente para excavadoras en operaciones de excavación y carga. Su excepcional diseño de pared lateral, con un reborde que sobresale, permite el contacto estrecho entre dos neumáticos, lo que elimina la necesidad de un anillo de caucho especial para evitar la penetración de piedras. El exclusivo diseño de la banda de rodadura proporciona una tracción superior en condiciones exigentes. Otras prestaciones de EM 933 SUPER son el excelente confort de conducción y las propiedades de autolimpieza mejoradas.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Pala excavadora

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	OW	OD	Type
290/90 - 20	STANDARD	94070183	E2	152 B / 168 A2	18	8.00		11.6	41.5	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..