

## EM 937 E3 (L) - Especificaciones técnicas



### Description

EM 937 (E-3/L-3) ha sido particularmente proyectado para los dúmpers rígidos que se utilizan en las minas a cielo abierto. Este neumático ofrece una excelente durabilidad, así como una elevada resistencia a los cortes y los desgarros. EM 937 (E-3/L-3) es particularmente idóneo para las operaciones de trabajo más pesadas.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Industrial: Cargadora retroexcavadora • Pala cargadora

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

## Dimensions International Standard

Ply Rating	20
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	620
Rolling Circumference (mm)	4105
Rim Rec	10.00/1.5
TRA Code	E3/L3

## Load capacity (Kg)

km/h / bar	4.75	7.00
50	4625	-
10	-	8500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 6:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..