

FARM 2000 PLUS - Especificaciones técnicas



Description

FARM 2000 PLUS es un neumático agrícola que se distingue por el número elevado de los tacos, que garantiza una mejor prestación en las operaciones realizadas en el campo. La profunda banda de rodadura asegura una amplia vida del neumático y excelente tracción, mientras que la mezcla superior de la banda de rodadura se traduce en una óptima resistencia a los cortes y los desgarres. FARM 2000 PLUS muestra extraordinarias cualidades de auto-limpieza, así como un diseño particular de los ángulos de los tacos que hace que sea idóneo para las actividades en el campo y de transporte.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28
LI/SS	139 A8

Dimensions US Standard

Usa code	94043750
Ply Rating	12
Section Width (inch)	17.3
Overall Diameter (inch)	56.5
Static Loaded Radius (inch)	25.9
Rolling Circumference (inch)	169.7
Rim Rec	W 15 L
Rim Alt	W 14 L
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..