

FARM 2000 - Especificaciones técnicas



Description

FARM 2000 es el neumático ideal para los tractores que se utilizan tanto en los trabajos del campo. Ha sido proyectado con una mezcla particularmente resistente a los cortes y los desgarres que asegura una durabilidad superior. Gracias a la carcasa robusta, FARM 2000 ofrece una elevada capacidad de carga así como excelentes propiedades de auto-limpieza.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	14.9 - 28
LI/SS	130 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	385
Overall Diameter (mm)	1375
Static Loaded Radius (mm)	636
Rolling Circumference (mm)	4194
SRI (mm)	650
Rim Rec	W 13
Rim Alt	W 11 ; W 12
ECE	E11-106R-004375
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.80
30	1900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..