

## FL 252 - Especificaciones técnicas



### Description

FL 252 es el neumático ideal para las operaciones de recolección de forraje con rastrillos hileradores y volteadoras de heno, así como para las operaciones logísticas con carretillas elevadoras. Este neumático garantiza una excelente duración, mientras que el específico dibujo de la banda de rodadura asegura la máxima estabilidad durante las operaciones de elevación.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Rastrillo hilerador rotativo  
Industrial: Carretilla elevadora

Version	STANDARD
Type	TT
Tyre Size	7.00 - 12

## Dimensions US Standard

Usa code	94006892
Ply Rating	14
Section Width (inch)	7.6
Overall Diameter (inch)	26.9
Rim Rec	5.00 S

## Load capacity (lbs)

mph / psi	131
15 LOAD WHEEL	6075
15 STEER WHEEL	4675
5 OTHER VEHICLES	6075
15 OTHER VEHICLES	4675
STATIC SIDE LOADER	7055

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..