

# FL 630 SUPER - Especificaciones técnicas



## Description

FL 630 SUPER es un neumático de flotación particularmente idóneo para utilizarlo con remolques, auto cisternas y pulverizadores. Su estructura resistente proporciona una excelente tracción y un agarre perfecto incluso en las curvas y durante las maniobras. El particular dibujo de la banda de rodadura garantiza una perfecta adherencia en cualquier tipo de terreno, así como avanzadas propiedades de auto-limpieza. FL 630 SUPER permite velocidades hasta 70 km/h.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

|                    |               |
|--------------------|---------------|
| Version            | STANDARD      |
| Type               | TL            |
| Tyre Size          | 850/50 R 30.5 |
| LI/SS              | 182 D         |
| LI/SS DRIVE WHEEL  | 182 D         |
| LI/SS FREE ROLLING | 182 D         |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 860             |
| Overall Diameter (mm)      | 1625            |
| Static Loaded Radius (mm)  | 722             |
| Rolling Circumference (mm) | 4895            |
| SRI (mm)                   | 775             |
| Rim Rec                    | AG 28.00        |
| ECE                        | E11-106R-008232 |

## Load capacity (Kg)

| km/h / bar | 1.2  | 1.6  | 2.0  | 2.4   | 2.8   | 3.2   | 3.6   | 4.0   |
|------------|------|------|------|-------|-------|-------|-------|-------|
| 70         | 3175 | 3945 | 4490 | 5185  | 5880  | 6425  | 7040  | 7735  |
| 65         | 3485 | 4335 | 4930 | 5695  | 6460  | 7055  | 7735  | 8500  |
| 50         | 4220 | 5250 | 5970 | 6895  | 7820  | 8540  | 9360  | 10285 |
| 40         | 4740 | 5900 | 6705 | 7750  | 8790  | 9595  | 10520 | 11560 |
| 25         | 5510 | 6850 | 7790 | 9000  | 10210 | 11150 | 12225 | 13430 |
| 10         | 6275 | 7805 | 8875 | 10255 | 11630 | 12700 | 13925 | 15300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 20:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..