

## FL 630 ULTRA - Especificaciones técnicas



### Description

FL 630 ULTRA es un neumático de flotación idóneo para utilizarlo tanto en el campo como por carretera, con remolques, auto cisternas y pulverizadores. Gracias al talón reforzado y el dibujo particular de la banda de rodadura, el neumático es ideal para un uso polivalente en cualquier terreno y por carretera. FL 630 ULTRA es sinónimo de una compactación del suelo extraordinariamente reducida.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	159 D/170 A8

## Dimensions US Standard

Usa code	94054220
Section Width (inch)	24.1
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	20.4
Rolling Circumference (inch)	139.1
Rim Rec	AG 20.00
ECE	E11-106R-003960

## Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	2820	3260	3690	4450	5190	5910	6660	7340	8090	8780
40	3090	3570	4060	4890	5700	6500	7300	8070	8870	9640
30	3740	4320	4910	5950	6890	7880	8820	9740	10750	11670
25	4230	4890	5560	6700	7800	8930	10040	11070	12170	13230
15	4880	5640	6400	7740	8990	10310	11490	12790	14030	15240
5	5560	6430	7300	8820	10250	11740	13090	14550	15970	17360

Printed on 02/07/2024 11:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..