

FLOTATION TR 678 - Especificaciones técnicas



Description

FLOTATION TR 678 ha sido particularmente desarrollado para la maquinaria agrícola y los remolques tanto para carretera como fuera de carretera. Permite transportar cargas pesadas a bajas presiones, asegurando al mismo tiempo una reducida compactación del suelo. Este neumático garantiza una excelente tracción y óptimas propiedades de auto-limpieza.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	500/45 - 20
LI/SS DRIVE WHEEL	148 A8
LI/SS FREE ROLLING	160 A8

Dimensions US Standard

Usa code	94068906
Section Width (inch)	19.5
Overall Diameter (inch)	38.6
Rim Rec	16.00 DC
ECE	E11-106R-006816

Load capacity (lbs)

mph / psi	87
25	9920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..