

FS 216 - Especificaciones técnicas



Description

FS 216 se caracteriza por el robusto dibujo de los tacos, con una angulación optimizada y más ancha para potenciar las prestaciones relativas a la tracción en los vehículos **forwarder** (autocargadores) y las máquinas arrastradoras (**skidder**). Este neumático ofrece una excelente resistencia a los cortes y los desgarres, incluso en las condiciones operativas más críticas, asegurando en todos los casos la máxima protección contra posibles daños.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Cosechadora forestal

Version	STEEL BELTED
Type	TL
Tyre Size	18.4 - 34

Dimensions International Standard

Ply Rating	14
Section Width (mm)	467
Overall Diameter (mm)	1679
Static Loaded Radius (mm)	768
Rolling Circumference (mm)	5042
Rim Rec	DW 16 A
ECE	E11-106R-003401
TRA Code	LS2

Load capacity (Kg)

km/h / bar	2.80	2.40
10	4875	-
30	-	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 1:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..