

FS 216 - Especificaciones técnicas



Description

FS 216 se caracteriza por el robusto dibujo de los tacos, con una angulación optimizada y más ancha para potenciar las prestaciones relativas a la tracción en los vehículos **forwarder** (autocargadores) y las máquinas arrastradoras (**skidder**). Este neumático ofrece una excelente resistencia a los cortes y los desgarres, incluso en las condiciones operativas más críticas, asegurando en todos los casos la máxima protección contra posibles daños.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Cosechadora forestal

Version	STEEL BELTED
Type	TT
Tyre Size	23.1 - 26

Dimensions US Standard

Usa code	94031795
Ply Rating	16
Section Width (inch)	23.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	28.6
Rolling Circumference (inch)	188.2
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-003661
TRA Code	LS2

Load capacity (lbs)

mph / psi	40	35
5	13900	-
20	-	9900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 1:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..