

HARVESTER SPECIAL - Ficha técnica



Description

HARVESTER SPECIAL ha sido especialmente proyectado para las cosechadoras. Los tacos de doble ángulo aseguran una excelente tracción en el campo y un extraordinario confort de guía por carretera. El especial diseño de la banda de rodadura ofrece un mayor contacto y una mejor estabilidad. HARVESTER SPECIAL se distingue por la robusta carcasa y una mezcla especialmente resistente contra los cortes y los desgarros, prolongando el ciclo de vida del neumático.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Cosechadora

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
23.5 - 25	DUAL BEAD	R1	191 A2	20	19.50/2.5		615	1665	715	5058	TL	E11-106R-006954
23.1 - 26	DUAL BEAD	R1	159 A6	16	DW 20 B ; DW 20 A		587	1585	720	4806	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..