

## IT 400 - Especificaciones técnicas



### Description

IT 400 es un neumático con un dibujo de bloques en la banda de rodadura que se utiliza principalmente por carretera en las actividades de transporte con plataformas bajas. Este neumático es idóneo para las aplicaciones de alta velocidad y garantiza significativos ahorros de carburante.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Remolque da plataforma baja

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15
LI/SS	125/121 J

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	210
<b>Overall Diameter (mm)</b>	795
<b>Static Loaded Radius (mm)</b>	356
<b>Rolling Circumference (mm)</b>	2361
<b>Rim Rec</b>	6.0
<b>Rim Alt</b>	5.50 F ; 6.50
<b>ECE</b>	E11-54R-0019535

## Load capacity (Kg)

km/h / bar	8.50	7.90
100 LS	1650	-
100 LD	-	1450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..