

LG 306 - Especificaciones técnicas



Description

LG 306 es un neumático para el césped y la jardinería, idóneo para segadoras. En algunas medidas, LG 306 también es adecuado para los minitractores. El específico dibujo de la banda de rodadura hace que este neumático sea delicado en el terreno, facilitando al mismo tiempo la manipulación y las maniobras. LG 306 está disponible en una versión "aramid-belted", con cinturones de aramida, para usuarios que requieren una mayor resistencia a la perforación.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Segadora • Minitractor

Version	STANDARD
Type	TL
Tyre Size	18 X 8.50 - 10

Dimensions International Standard

Ply Rating	4
Section Width (mm)	210
Overall Diameter (mm)	460
Static Loaded Radius (mm)	206
Rolling Circumference (mm)	1370
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003452

Load capacity (Kg)

km/h / bar	1.50
15	361

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 6:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..