

LG RIB PLUS - Especificaciones técnicas



Description

LG RIB PLUS es un neumático para césped y jardín adecuado para aplicaciones con cortacéspedes, pequeños tractores y henificadoras.

El dibujo de la banda de rodadura se ha diseñado especialmente para que el neumático sea suave con el suelo y evite daños en el césped, a la vez que facilita la maniobrabilidad.

Gracias al perfil redondo, LG RIB PLUS puede deslizarse y arrastrar fácilmente al girar en el campo.

UM

International Standard

Construction

BIAS

Machinery

Agricultura: Segadora • Minitractor

Version	STANDARD
Type	TL
Tyre Size	16 X 6.50 - 8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	170
Overall Diameter (mm)	408
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90

Load capacity (Kg)

km/h / bar	4.90
15	480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 0:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..