

## LG RIB - Ficha técnica



### Description

LG RIB es un neumático para el césped y la jardinería, idóneo para segadoras y minitractores. El específico dibujo de la banda de rodadura hace que este neumático sea delicado en el terreno, previniendo daños al prado facilitando al mismo tiempo la manipulación y las maniobras. LG RIB está disponible en una versión "aramid belted", con cinturones de aramida, para usuarios que requieren una mayor resistencia a la perforación.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Segadora • Minitractor

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11 X 4.00 - 5	STANDARD	94074686	39 A6	4	3.00 A		4.1	10.7	0	0	TL	E11-106R-008779
13 X 5.00 - 6	ARAMID BELTED	94013012		6	3.50 A		5	12.8	5.7	37.1	TL	E11-106R-005221
13 X 5.00 - 6	STANDARD	94012930		4	3.50 A		5	12.8	5.7	37.1	TL	E11-106R-003465
15 X 6.00 - 6	ARAMID BELTED	94013029		6	4.50 A		6	14.4	6.3	41.7	TL	E11-106R-003504
15 X 6.00 - 6	STANDARD	94012954		4	4.50 A		6	14.4	6.3	41.7	TL	E11-106R-003466
15 X 6.00 - 6	STANDARD	94012961		6	4.50 A		6	14.4	6.3	41.7	TL	E4-106R-002173
16 X 6.50 - 8	ARAMID BELTED	94052165		10	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	E11-106R-005404
16 X 6.50 - 8	ARAMID BELTED	94013036		6	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	E11-106R-003499
16 X 6.50 - 8	STANDARD	94041701		8	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	
16 X 6.50 - 8	STANDARD	94030866		10	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	E4-106R-003372
16 X 6.50 - 8	STANDARD	94012978		4	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TT	E11-106R-003467
16 X 6.50 - 8	STANDARD	94012985		4	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	E11-106R-003467
16 X 6.50 - 8	STANDARD	94013005		6	5.375 I - 55; I - 70; I - 90		6.7	16.1	7.2	46.6	TL	E11-106R-003468
20 X 10.00 - 10	STANDARD	94026128		4	8.00 I - 55; I - 70; I - 90	7.00 I - 55; I - 70; I - 90	9.3	19.6	8.7	56.9	TL	E11-106R-003469

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..