

LG SMOOTH - Especificaciones técnicas



Description

LG SMOOTH es un neumático para el césped y la jardinería, idóneo para segadoras. Este neumático es delicado en el terreno y además su avanzado dibujo asegura una incrementada durabilidad, facilitando la manipulación y las maniobras. LG SMOOTH está disponible en una versión "aramid-belted", con cinturones de aramida, para usuarios que requieren una mayor resistencia a la perforación.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Segadora • Minitractor

Version	ARAMID BELTED
Type	TL
Tyre Size	16 X 6.50 - 8

Dimensions US Standard

Usa code	94065523
Ply Rating	10
Section Width (inch)	6.3
Overall Diameter (inch)	15.7
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90

Load capacity (lbs)

mph / psi	71
10	1035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..